



Adjustable central bearing hinge with adapter - gap 4/12, axis 8,5, 9 and 13, rebate 15, 18 and 20 mm

Pressure adjustment

X	Axis	Rebate
26	8,5	15
29	8,5	18
29	13	18
31	9	20
31	13	20



Description

Non-handed adjustable bearing hinge with adapter.

Application

For all types of wooden doors/windows, gap 4/12 mm, axis 8,5, 9 and 13, rebate 15, 18, and 20 mm. To use in combination with stay supports.

Applied in eurogroove 16/12 of the sash, it can be used in the following ways:

- 1) as a main hinge replacing traditional screw hinges, on side-hung systems;
- 2) for doors and window that require one or more locking points on the second sash of tilt and turn systems, placed between the corner hinge and top hinge;
- 3) for tilt only doors and windows.

The friction allows the sash to remain in the desired position, by compensating for any offset caused by over adjustments or out of square walls.

Adjustment

With 4 mm hexagonal wrench:

- 1 lateral adjustment ± 3 mm;
- 2 height adjustment $\pm 2,5$ mm, by loosening the fixing screws in the slots of the support plate you can lower or raise the sash.
- 3 +1 mm pressure adjustment, by screwing the central screw the corner can be removed and rotated 180°, thus gaining + 1 mm of pressure compared to the nominal axis.

Mounting

4x40 mm screws.

Example of application gap 12 mm

Axis 9, rebate 18 mm

Axis 13, rebate 18 mm

Order Specifications

Article	Axis	Rebate
A51102.22.02	8,5	15
A51102.24.02	9	18
A51102.26.02	9	20
A51102.34.02	13	18
A51102.36.02	13	20